



INSULADD ENERGY SAVING PAINT ADDITIVE

<p><u>PRODUCT DESCRIPTION</u></p> <p>Insuladd Energy Saving Paint Additive is a uniquely treated fine white powdered ceramic material specifically engineered to improve the effective insulation of the surfaces to which it has been applied. Once applied, it acts as a radiant heat reflecting barrier that improves comfort, reduces heating and cooling requirements and dampens ambient noise.</p> <p><u>FEATURES</u></p> <ul style="list-style-type: none"> • Reduce heating and cooling • Superior radiant barrier • Mixes with any paint • No lead pigments • Safe / Non-Toxic • Improve comfort • Energy efficient • Dampen sound • <p><u>USES</u></p> <ul style="list-style-type: none"> • Drywall • Plaster • Masonry • Wood • Metal • Interior Walls • Interior Ceilings 	<p><u>SPECIFICATIONS</u></p> <ul style="list-style-type: none"> • Colors: White • Finish: Smooth Flat • Flash Point: N/A • Method Used: T.C.C. • Coating: VOC N/A • Volume Solids 100% Weight Solids 100% • Recommended Mil Film: Read Paint Specs • Estimated Coverage: Read Paint Specs • Data Pigment: N/A • Vehicle: N/A • Cleanup: Read Paint Specs • Thinning: Read Paint Specs • Estimated Dry Time: Read Paint Specs • 2 Coats Recommended 	<p><u>SURFACE PREPARATION</u></p> <p>PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN! Keep away from heat, sparks and open flames. USE WITH ADEQUATE VENTILATION! Where ventilation is inadequate, use a suitable respirator. Avoid prolonged contact with skin and breathing of vapors and/or spray mists. When spraying this material, use an OSHA approved cartridge respirator. Use chemical safety glasses, goggles, or a face shield for proper eye protection. Wash thoroughly after handling and before eating, drinking, or smoking. Close container after each use. DO NOT TAKE INTERNALLY! FIRST AID: In case of skin contact, wash thoroughly with plenty of warm soapy water. For eye contact, flush with plenty of water for 15 minutes, SEEK MEDICAL ATTENTION! If affected by inhalation, move immediately to fresh air. If swallowed, DO NOT INDUCE VOMITING, SEEK IMMEDIATE MEDICAL ATTENTION!</p> <p>WARNING: Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in U.S.) or contact your local health authority.</p>
---	---	--



INSULADD ENERGY SAVING PAINT ADDITIVE

SURFACE PREPARATION

GENERAL: The entire surface area to be painted should be clean, dry, sound, and free from all dirt, grease, oils, waxes, mildew and any other surface contaminants. Surface areas affected by mildew growth should be properly scrubbed with a soft-medium bristle scrub brush and a solution of one (1) cup Tri-Sodium Phosphate (TSP) mixed with one (1) quart household bleach and three (3) quarts of warm water, per gallon solution. Allow solution to stand on the affected surface areas for approximately 10-20 minutes, then rinse thoroughly with clean water and allow 24-48 hours to dry properly.

Remove any loose scale, chalked, cracked or peeling paint from previously painted substrates by hand scraping, sanding, wire brushing, and or power tool cleaning. Previously painted substrates that show signs of severe delaminated surfaces should be completely stripped down to a more suitable and or stable substrate. Repair / replace any damaged and or delaminated surface areas. Lightly sand smooth all rough paint edges to the adjacent surface area and sand all glossy surfaces to effectively dull any existing sheen levels.

PRODUCT APPLICATION

Apply when surface and ambient temperatures are above 55/F. and below 90/F.

KEEP PRODUCT FROM FREEZING!

Apply with a quality brush, roller, or airless spray equipment.

For best results, apply with a brush and/or roller effectively working into surface pores. If applying with a brush, apply a smooth and generous coat application on smaller surface areas, such as trim or cutting-in larger surface areas. If applying with a roller cover, apply an even and generous coat application in an "M" or crisscross motion, avoiding any excessive re-spreading or reworking. Always maintain a proper wet edge by brushing/rolling into previously applied coating area. If using a spray application method, the surface areas should be properly back-rolled to effectively work into surface pores, ensure proper adhesion and an even coat application.

All application methods are approximate. Application procedures may be contingent upon specifications of the paint used in conjunction with this product.

METHOD

Brush: Synthetic
 Roller: 3/8"-1/2" Nap
 Airless Spray: Minimum 2000 psi
 Tip: 0.017"-0.019"

CLEANUP

Spills, splatters, tools, and equipment easily cleanup with warm soapy water. Be sure to flush all tools and equipment used in the application process with warm soapy water.

IMPORTANT

ALL TECHNICAL DATA INFORMATION CONTAINED HEREIN IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. ALL WARRANTIES ARE EXCLUDED, WHETHER EXPRESSED OR IMPLIED BY OPERATION OF LAW OR OTHERWISE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, SELLER SHALL NOT BE LIABLE, (DIRECTLY OR INDIRECTLY), UNDER ANY CIRCUMSTANCES FOR CONSEQUENTIAL, INCIDENTAL, SPECIAL OR ANY OTHER TYPE OF DAMAGES ARISING OR RESULTING FOR ANY REASON UNDER THE SALE, HANDLING, OR USE OF GOODS SOLD. SELLER'S LIABILITY HEREUNDER, AND BUYER'S EXCLUSIVE REMEDY HEREUNDER, FOR NEGLIGENCE OR ANY OTHER REASON, IS EXPRESSLY LIMITED TO REIMBURSEMENT OF THE PURCHASE PRICE OF THE MATERIALS SOLD AFTER PROOF OF PURCHASE IS PROVIDED TO THE SELLER. NOTICE OF ANY ALLEGED FAILURE OR DEFECT IN THE MATERIALS MUST BE GIVEN TO THE SELLER IN WRITING BY CERTIFIED U.S. MAIL WITHIN 15 DAYS OF FIRST NOTICING THE PROBLEM. FAILURE TO GIVE THE REQUIRED NOTICE WITHIN THE TIME PROVIDED CONSTITUTES A WAIVER OF ANY CLAIM. THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY MISREPRESENTATION MADE BY THE DEALER.

NOTE THAT INFORMATION WITHIN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. PLEASE CONSULT YOUR DEALER OR REPRESENTATIVE FOR THE MOST RECENT REVISIONS OF THIS INFORMATION.